

ECK11120

ADAPTOR TURNABLE PLUG WITH LUMINOUS SWITCH

Residential > Utility series > Items for domestic use > Adaptors > Socket outlet combination > Triple adaptor 16 a - with light switch

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

CEI 23-50 CEI 23-151

Description

16A triple system adapter with illuminated switch. 16A 2P+E rotating plug, type S17. 10/16A 2P+E sockets type P17/11 + 10/16A Schuko/dual-standard socket type P17/11-30. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	**RAL-number (similar)**	9003	**Material**	Plastic
Material quality	Thermoplastic	**Halogen free**	No	**Anti-bacterial treatment**	No
Surface protection	Untreated	**Surface finishing**	Glossy	**Colour**	White
Transparent	No	**Impact strength**	IK09	**Working temperature**	-15 ÷ 35 °C
Compatible with Apple HomeKit	No	**Compatible with Google Assistant**	No	**Compatible with Amazon Alexa**	No
IFTTT support available	No	**Overvoltage protection**	No	**With miniature fuse**	No
With on/off switch	Yes	**Rotated central insert**	No	**Nominal current**	16 A
Number of socket outlets with protective contact CEE 7/3 (type F)	1	**Number of socket outlets British Standard BS 1363**	0	**Number of socket outlets Italian standard type Bipasso**	3
Number of socket outlets Italian standard type P11	0	**Number of socket outlets Italian standard type P17**	0	**Number of socket outlets Italian standard type P30**	0
Number of universal multi standard sockets	0	**Number of socket outlets Swiss standard type 13**	0	**Number of socket outlets Swiss standard type 15**	0
Number of socket outlets Swiss standard type 23	0	**Number of socket outlets Swiss standard type 25**	0	**Type of mains connection**	Italian type P17
NEMA designation	None	**Housing shape**	Rectangular	**Number of socket outlets CEE 7/1 (no protective contact)**	0
Number of socket outlets CEE 7/16 (EURO)	0	**Number of socket outlets with earth pin**	3	**Number of cold device socket outlets**	0
Number of socket outlets Danish standard (earthing pin, type K)	3	**Number of socket outlets with protective contact CEE 7/5 (type E)**	0	**Number of NEMA-outlets**	0
Residual current circuit breaker (RCCB)	No	**Mains filter**	No	**Number of other socket outlets**	0
Number of USB connections	0	**Overcurrent protection**	No	**Max. connected load**	3500 W
With cover	No	**Type of plug**	Straight	**Directly pluggable (without power cord)**	Yes

Barcode

8033954877758

Unit

1 NR

0.1292 [kg]

8057711595242

Pack

12 NR

0.14x0.445x0.135 [m]

1.5504 [kg]

8032793871118

Cardboard

48 NR

0.305x0.47x0.295 [m]

6.2016 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.