

# ECK11310N

## DESK MULTIPLE SOCKET +2 X USB 4 BI-POWER +1 SCHUKO - BLACK

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > Desk multiple socket base with cable

### Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

### Norms

CEI 23-50 CEI 23-124

## Description

USB desktop power strip with cable, plug, thermal circuit breaker, and individual illuminated switches. 4 dual-standard sockets 2P+E 10/16A type P17/11. 1 Schuko/dual-standard socket 10/16A type P17/11-30. 2 USB ports 1000 mA x 2 with LED indicator. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Black color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 2.0 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC000330 - Socket outlet combination

| | | | | | |
|---|---|---|---|---|---|
| **Degree of protection (IP)** | IP20 | **RAL-number (similar)** | 9005 | **Material** | Plastic |
| **Material quality** | Thermoplastic | **Halogen free** | No | **Anti-bacterial treatment** | No |
| **Surface protection** | Untreated | **Surface finishing** | Glossy | **Colour** | Black |
| **Transparent** | No | **Impact strength** | IK09 | **Working temperature** | -15 ÷ 35 °C |
| **Compatible with Apple HomeKit** | No | **Compatible with Google Assistant** | No | **Compatible with Amazon Alexa** | No |
| **IFTTT support available** | No | **Overvoltage protection** | No | **With miniature fuse** | No |
| **With on/off switch** | Yes | **Rotated central insert** | No | **Nominal current** | 16 A |
| **Core cross section** | 1 mm² | **Number of socket outlets with protective contact CEE 7/3 (type F)** | 1 | **Number of socket outlets British Standard BS 1363** | 0 |
| **Number of socket outlets Italian standard type Bipasso** | 4 | **Number of socket outlets Italian standard type P11** | 0 | **Number of socket outlets Italian standard type P17** | 0 |
| **Number of socket outlets Italian standard type P30** | 0 | **Number of universal multi standard sockets** | 0 | **Number of socket outlets Swiss standard type 13** | 0 |
| **Number of socket outlets Swiss standard type 15** | 0 | **Number of socket outlets Swiss standard type 23** | 0 | **Number of socket outlets Swiss standard type 25** | 0 |
| **Type of mains connection** | Italian type P17 | **NEMA designation** | None | **Housing shape** | Rectangular |
| **Number of socket outlets CEE 7/1 (no protective contact)** | 0 | **Number of socket outlets CEE 7/16 (EURO)** | 0 | **Number of socket outlets with earth pin** | 5 |
| **Number of cold device socket outlets** | 0 | **Number of socket outlets Danish standard (earthing pin, type K)** | 0 | **Number of socket outlets with protective contact CEE 7/5 (type E)** | 0 |
| **Number of NEMA-outlets** | 0 | **Residual current circuit breaker (RCCB)** | No | **Mains filter** | No |
| **Number of other socket outlets** | 0 | **Number of USB connections** | 2 | **Overcurrent protection** | Yes |
| **Max. connected load** | 3500 W | **With cover** | No | **Length of power cord** | 1.5 m |
| **Type of plug** | Straight | **Directly pluggable (without power cord)** | No | | |

## Barcode

8053676577804

**Unit**

1 NR

0.46 [kg]

8059307219686

**Cardboard**

30 NR

0.4x0.47x0.3 [m]

13.8 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.