

# ECK33416

## SOCKET BLACK BI-POWER SCHUKO 10/16A

Residential > Utility series > Items for domestic use > Plugs and sockets > Socket with earthing > Mobile socket - schuko

### Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

### Norms

CEI 23-50

## Description

10/16A 2P+E dual-standard Schuko rewirable socket, type P17-11-P30. Black color. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Shuttered outlets for protection against accidental contact. Protective cable sleeve and cord grip with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC001327 - Coupler with protective contact

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 3 | **Degree of protection (IP)** | IP20 | **Material** | Plastic |
| **Material quality** | Thermoplastic | **Halogen free** | Yes | **Colour** | Black |
| **Model** | Coupler CEE 7/3 (Typ F) | **RAL-number** | 9005 | **Nominal voltage** | 250 V |
| **Nominal current** | 16 A | **For heavy conditions according to VDE** | No | **Connection system** | Screwed terminal |
| **Insert direction** | Straight | **With voltage indication** | No | **With quick-lock** | No |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8054320289616

**Pack**

20 NR

21.14 [kg]



8057711595525

**Cardboard**

200 NR

0.305x0.545x0.245 [m]

211.4 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.