elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECK33417

TRIPLE ADAPTOR BLACK

Residential > Utility series > Items for domestic use > Adaptors > Plug adapter > Triple schuko adaptor

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | MADE IN PRC

Norms

CEI 23-50 CEI 23-57

Description

16A triple system adapter. 16A 2P+E plug type S17. 10/16A 2P+E sockets type P17/11 + 16A Schuko/dual-standard socket type P17/11-30. Black color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001513 - Plug adapter

Colour	Black	**Model**	Compact	**Nominal voltage**	200 ÷ 250 V
With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I)	No	**With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F)**	No	**With plug for BE/DE/NL/RU/CH (Euro) (type C)**	No
With plug for CH (SEV 1011 type 11) (type J)	No	**With plug for CH (SEV 1011 type 12) (type J)**	No	**With plug for CH (SEV 1011 type 23) (type J)**	No
With plug for FR (earth pin) (type E)	No	**With plug for UK/HK (BS 1363) (type G)**	No	**With plug for IT (S/P 11)**	No
With plug for IT (S/P 17) (type L)	Yes	**With plug for US/CA/CN (NEMA 1-15) (type A)**	No	**With plug for US/CA/CN (NEMA 5-15) (type B)**	No
Type of bus	Other	**Number of USB ports**	0	**Nominal current**	16 ÷ 16 A

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054320289609

Pack

20 NR

1.15 [kg]



8057711595532

Cardboard

200 NR

0.275x0.235x23.5 [m]

11.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.