

ECK33512

SOCKET BLACK 10A 2P+E

Residential > Utility series > Items for domestic use > Plugs and sockets > Socket with earthing > Mobile socket - axial output

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

CEI 23-50

Description

10A 2P+E rewirable socket, type P11. Black color. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Shuttered outlets for protection against accidental contact. Protective cable sleeve and cord grip with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001327 - Coupler with protective contact

Number of poles	3	**Degree of protection (IP)**	IP20	**Material**	Plastic
Material quality	Thermoplastic	**Halogen free**	Yes	**Colour**	Black
Model	Italian type P11	**RAL-number**	9003	**Nominal voltage**	250 V
Nominal current	10 A	**For heavy conditions according to VDE**	No	**Connection system**	Screwed terminal
Insert direction	Straight	**With voltage indication**	No	**With quick-lock**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054320289500

Pack

20 NR

0.66 [kg]

8057711595631

Cardboard

200 NR

0.21x0.295x0.255 [m]

6.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.