

ECK33601

PLUG 10A 2P+E WHITE S11

Residential > Utility series > Items for domestic use > K336 - plugs, sockets and flow pack adaptors > Plug with earthing > Mobile plug - axial output

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | RoHS II | MADE IN PRC

Norms

CEI 23-50

Description

10A 2P+E mobile plug, type S11. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Protective cable gland and cable clamp with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000242 - Plug with protective contact

Number of poles	3	**Degree of protection (IP)**	IP20	**Material**	Plastic
Material quality	Thermoplastic	**Colour**	White	**Model**	Italian type P11
Nominal voltage	250 V	**Protective contact**	Round	**Nominal current**	10 A
For heavy conditions according to VDE	No	**Connection system**	Screwed terminal	**Insert direction**	Straight
Adaptor plug	No				

Documentation available for download



Certification

IMQ_CA02.06290_2018-07-11.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054382041146
Unit
1 NR
0.023 [kg]

8059307219921
Cardboard
100 NR
0.24x0.26x0.12 [m]
2.3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.