

ECK33612

SOCKET 10A 2P+E BLACK P11

Residential > Utility series > Items for domestic use > K336 - plugs, sockets and flow pack adaptors > Socket with earthing > Mobile socket - axial output

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | RoHS II | MADE IN PRC

Norms

CEI 23-50

Description

10A 2P+E mobile socket, type P11. Black color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Sockets protected against accidental contact. Protective cable gland and cable clamp with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001327 - Coupler with protective contact

Number of poles	3	**Degree of protection (IP)**	IP20	**Material**	Plastic
Material quality	Thermoplastic	**Halogen free**	Yes	**Colour**	Black
Model	Italian type P11	**RAL-number**	9011	**Nominal voltage**	250 V
Nominal current	10 A	**For heavy conditions according to VDE**	No	**Connection system**	Screwed terminal
Insert direction	Straight	**With voltage indication**	No	**With quick-lock**	No

Documentation available for download



Certification

IMQ_CA02.06292_2018-07-11.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054382041191
Unit
1 NR
0.037 [kg]

8059606150031
Cardboard
100 NR
0.255x0.255x0.19 [m]
3.7 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.