

ECK33616

3 WAY ADAPTER 16A 2P+E BLACK S17-P17/11

Residential > Utility series > Items for domestic use > K336 - plugs, sockets and flow pack adaptors > Plug adapter > Triple adaptor - blister

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

CEI 23-57

Description

16A triple adapter. 16A 2P+E plug type S17. 10/16A 2P+E sockets type P17/11. Black color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001513 - Plug adapter

Colour	Black	**Model**	Compact	**Nominal voltage**	200 ÷ 250 V
With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I)	No	**With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F)**	No	**With plug for BE/DE/NL/RU/CH (Euro) (type C)**	No
With plug for CH (SEV 1011 type 11) (type J)	No	**With plug for CH (SEV 1011 type 12) (type J)**	No	**With plug for CH (SEV 1011 type 23) (type J)**	No
With plug for FR (earth pin) (type E)	No	**With plug for UK/HK (BS 1363) (type G)**	No	**With plug for IT (S/P 11)**	No
With plug for IT (S/P 17) (type L)	Yes	**With plug for US/CA/CN (NEMA 1-15) (type A)**	No	**With plug for US/CA/CN (NEMA 5-15) (type B)**	No
Type of bus	IT (S/P 17) (type L)	**Number of USB ports**	0	**Nominal current**	10 ÷ 16 A

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054382041290

Unit

1 NR

0.062 [kg]



8059606150079

Cardboard

50 NR

0.25x0.26x0.195 [m]

3.1 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.