

ECK33624

SOCKET 10/16A 2P+E WHITE P17-11-30

Residential > Utility series > Items for domestic use > K336 - plugs, sockets and flow pack adaptors > Socket with earthing > Mobile socket - schuko

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

CEI 23-50

Description

10/16A 2P+E dual-standard Schuko mobile socket, type P17-11-P30. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Sockets protected against accidental contact. Protective cable gland and cable clamp with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001327 - Coupler with protective contact

Number of poles	3	**Degree of protection (IP)**	IP20	**Material**	Plastic
Material quality	Thermoplastic	**Halogen free**	Yes	**Colour**	White
Model	Coupler CEE 7/3 (Typ F)	**RAL-number**	9010	**Nominal voltage**	250 V
Nominal current	16 A	**For heavy conditions according to VDE**	No	**Connection system**	Screwed terminal
Insert direction	Straight	**With voltage indication**	No	**With quick-lock**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054382042044

Unit

1 NR

0.06 [kg]



8059606150154

Cardboard

50 NR

0.29x0.29x0.17 [m]

3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.