elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



# ECK33634

## SOCKET 10/16A 2P+E BLACK P17-11-30

Residential > Utility series > Items for domestic use > K336 - plugs, sockets and flow pack adaptors > Socket with earthing > Mobile socket - schuko

### Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

### Norms

CEI 23-50

## Description

10/16A 2P+E dual-standard Schuko mobile socket, type P17-11-P30. Black color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Sockets protected against accidental contact. Protective cable gland and cable clamp with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC001327 - Coupler with protective contact

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 3 | **Degree of protection (IP)** | IP20 | **Material** | Plastic |
| **Material quality** | Thermoplastic | **Halogen free** | Yes | **Colour** | Black |
| **Model** | Coupler CEE 7/3 (Typ F) | **RAL-number** | 9011 | **Nominal voltage** | 250 V |
| **Nominal current** | 16 A | **For heavy conditions according to VDE** | No | **Connection system** | Screwed terminal |
| **Insert direction** | Straight | **With voltage indication** | No | **With quick-lock** | No |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8054382042051

**Unit**

1 NR

0.06 [kg]



8059606150192

**Cardboard**

50 NR

3 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.