

ECK51006

PORTABLE HALOGEN PROJECTOR IP54 500W WITH SUPPORT

Residential > Utility series > Lighting > Floodlights > Building site lighting luminaire > Building site lighting luminaire

Technical Symbols/Marks/Approvals

IP65 | RoHS II | MADE IN PRC

Description

Floodlight with halogen lamp. Made of black-painted die-cast aluminum. Adjustable and swiveling yellow-painted steel support. Hammered aluminum reflector. Rated voltage: 250V~. Included lamp power: 500W. Type S31 Schuko plug. H05RN-F 3G1 VDE cable. Length: 1.5 m. Protection rating: IP54.

Etim

GROUP EG000027 - Luminaires

CLASS EC000346 - Building site lighting luminaire

Degree of protection (IP)	IP54	**Impact strength**	IK09	**Width**	180 mm
Height	145 mm	**Depth**	150 mm	**Nominal voltage**	220 ÷ 240 V
Connection type	Other	**With light source**	Yes	**Housing material**	Aluminium
Protection class according to IEC 61140	II	**Lamp holder**	R7s	**Lamp type**	LV halogen lamp
Housing colour	Black	**Colour of light**	White	**With socket outlet**	No
Energy efficiency class of the light source according to 2019/2015/EU	C	**With wheels**	No	**With stand holder**	No
With stand	No	**Colour of stand**	Yellow	**With protective cover**	Yes
Material protective cover	Steel	**Rated lifetime L70/B50 at 25 °C**	2000 h	**Suitable for lamp power**	500 ÷ 500 W
Max. system power	500 W	**Rated luminous flux according to IEC 62722-2-1**	8700 lm	**Colour temperature**	3000 ÷ 3000 K
Type of wiring	Ending	**Conductor cross section**	1 mm²	**Connection cable length**	1.3 m

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8033954877086

Unit

1 NR

2.1667 [kg]

8059606150253

Cardboard

8 NR

17.3336 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.