elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECK51007

PORTABLE LED PROJECTOR IP65 30W WITH SUPPORT

Residential > Utility series > Lighting > Floodlights > Building site lighting luminaire > Building site lighting luminaire

Technical Symbols/Marks/Approvals

IP65 | RoHS II | MADE IN PRC

Description

LED floodlight made of black-painted die-cast aluminum. Adjustable and swiveling yellow-painted steel support. Smooth aluminum reflector. Rated voltage: 240V~. LED module power: 30 W. Color temperature: cold white light. Brightness: 2700 lm. Type S31 Schuko plug. H05RN-F 3G1 VDE cable. Length: 1.5 m. Protection rating: IP65.

Etim

GROUP EG000027 - Luminaires

CLASS EC000346 - Building site lighting luminaire

Degree of protection (IP)	IP65	**Impact strength**	IK09	**Width**	190 mm
Height	145 mm	**Depth**	35 mm	**Nominal voltage**	220 ÷ 240 V
Connection type	Other	**With light source**	Yes	**Housing material**	Aluminium
Protection class according to IEC 61140	II	**Lamp holder**	None	**Lamp type**	LED not exchangeable
Housing colour	Black	**Colour of light**	White	**With socket outlet**	No
Energy efficiency class of the light source according to 2019/2015/EU	A	**With wheels**	No	**With stand holder**	No
With stand	No	**Colour of stand**	Yellow	**With protective cover**	No
Rated lifetime L70/B50 at 25 °C	20000 h	**Suitable for lamp power**	÷ W	**Max. system power**	30 W
Rated luminous flux according to IEC 62722-2-1	2700 lm	**Colour temperature**	6000 ÷ 6500 K	**Type of wiring**	Ending
Conductor cross section	1 mm²	**Connection cable length**	1.3 m		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8053676577941

Unit

1 NR

1.6667 [kg]

8059606150260

Cardboard

6 NR

0.245x0.5x0.285 [m]

10.0002 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.