



## ECK51018

### PROJECTOR LED 50W 220V IP65 CWITH STAND 950-1800 mm

Residential > Utility series > Lighting > Floodlights > Building  
site lighting luminaire > Led - with adjustable stand



#### Technical Symbols/Marks/Approvals



## Etim

### GROUP EG000027 - Luminaires

### CLASS EC000346 - Building site lighting luminaire

Degree of protection (IP)	IP65	Impact strength	IK09	Width	215 mm
Height	165 mm	Depth	38 mm	Nominal voltage	220-240 V
Connection type	Other	With light source	Yes	Housing material	Aluminium
Protection class according to IEC 61140	II	Lamp holder	None	Lamp type	LED not exchangeable
Housing colour	Black	Colour of light	White	With socket outlet	No
Energy efficiency class of the light source according to EU regulation 2019/2015	A	With wheels	No	With stand holder	Yes
With stand	Yes	Colour of stand	Yellow	With protective cover	No
Rated lifetime L70/B50 at 25 °C	20000 h	Suitable for lamp power	50-50 W	Rated luminous flux according to IEC 62722-2-1	4500 lm
Colour temperature	6500-6500 K	Type of wiring	Ending	Conductor cross section	1 mm²
Connection cable length	2.5 m				

## Barcode



8054382042570

#### Unit

1 NR

2.85 [kg]



8059606150284

#### Cardboard

4 NR

0.365x0.685x0.23 [m]

11.4 [kg]