

ECK51018

PROJECTOR LED 50W 220V IP65 CWITH STAND 950-1800 mm

Residential > Utility series > Lighting > Floodlights > Building site lighting luminaire > Building site lighting luminaire

Technical Symbols/Marks/Approvals

IP65 | RoHS II | MADE IN PRC

Description

LED floodlight made of black-painted die-cast aluminum. Adjustable tripod stand (950-1800 mm) made of yellow-painted steel. Smooth aluminum reflector. Rated voltage: 240V~. LED module power: 50 W. Color temperature: cold white light. Brightness: 4500 lm. Type S31 Schuko plug. H05RN-F 3G1 VDE cable. Length: 1.5 m. Protection rating: IP65.

Etim

GROUP EG000027 - Luminaires

CLASS EC000346 - Building site lighting luminaire

Degree of protection (IP)	IP65	**Impact strength**	IK09	**Width**	215 mm
Height	165 mm	**Depth**	38 mm	**Nominal voltage**	220 ÷ 240 V
Connection type	Other	**With light source**	Yes	**Housing material**	Aluminium
Protection class according to IEC 61140	II	**Lamp holder**	None	**Lamp type**	LED not exchangeable
Housing colour	Black	**Colour of light**	White	**With socket outlet**	No
Energy efficiency class of the light source according to 2019/2015/EU	A	**With wheels**	No	**With stand holder**	Yes
With stand	Yes	**Colour of stand**	Yellow	**With protective cover**	No
Rated lifetime L70/B50 at 25 °C	20000 h	**Suitable for lamp power**	50 ÷ 50 W	**Rated luminous flux according to IEC 62722-2-1**	4500 lm
Colour temperature	6000 ÷ 6500 K	**Type of wiring**	Ending	**Conductor cross section**	1 mm²
Connection cable length	2.5 m				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054382042570

Unit

1 NR

2.85 [kg]



8059606150284

Cardboard

4 NR

0.365x0.685x0.23 [m]

11.4 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.