elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECK51030

BATTERY CABLES 120A 2,5 m RED+BLACK

Residential > Utility series > Items for domestic use > Car battery clips and cables > Power cord

Description

120A Battery Jumper Cables Kit - High-capacity copper-clad aluminum (CCA) battery cables. Rated voltage: 24 V DC. Maximum allowable current: 120A. Cable cross-section: 10 mm². Length: 2.5 m. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Operating temperature: -15°C to +35°C. Insulated anti-corrosion clamps.

Etim

GROUP EG000053 - Batteries, chargers and power cords

CLASS EC001576 - Power cord

Length	2.5 m	**Material outer sheath**	Polyvinyl chloride (PVC)	**Colour outer sheath**	Other
Reaction-to-fire according to EN 13501-6: Class	Eca	**Reaction-to-fire according to EN 13501-6: Smoke production**	None	**Reaction-to-fire according to EN 13501-6: Flaming droplets/particles**	None
Reaction-to-fire according to EN 13501-6: Acidity	None	**Nominal voltage**	12 ÷ 24 V	**Number of cores**	2
Nominal cross section conductor	10 mm²	**Nominal current**	120 A	**With protective conductor**	No
Oil resistant according to EN IEC 60811-404	No	**Connection 1**	Other	**Cable entry connection 1**	Straight
Connection type according to IEC 60320, connection 1	Other	**Connection 2**	Other	**Cable entry connection 2**	Straight
Connection type according to IEC 60320, connection 2	Other	**System-oriented connector system**	No	**Spiralized cable**	No
With cord switch	No				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8053676578023
Unit
1 NR
9 [kg]

8059606150352
Cardboard
10 NR
0.255x0.465x0.245 [m]
90 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.