elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

ECK52002B

SWITCH 250V 2A 2X0,75 BLACK

Residential > Utility series > Lighting > Lamp switches > Cord switch

Technical Symbols/Marks/Approvals

IP40 | CE | RoHS II | MADE IN PRC

Norms

EN 61058-2-1

Description

In-line cord switch made of thermoplastic material. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 650°C. Rated voltage: 250 V~. Rated current: 2A resistive, 1A inductive, 1A tungsten lamp. Rated temperature: T55°C. Protection rating: IP20. Number of cycles: 10,000. Compatible cables: H03VVH2-F 2x0.5 / 0.75 mm².

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000445 - Cord switch/dimmer

RAL-number (similar)	9005	**Material**	Plastic	**Material quality**	Thermoplastic
Halogen free	No	**Surface protection**	Untreated	**Surface finishing**	Glossy
Colour	Black	**Transparent**	No	**Model**	Other
Operating method	Rocker	**Type of load**	Universal	**Compatible with Apple HomeKit**	No
Compatible with Google Assistant	No	**Compatible with Amazon Alexa**	No	**IFTTT support available**	No
Nominal voltage	250 V	**Nominal current**	2 A		

Technical Characteristics

Tipologia	Interruttore

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054320289432
Pack
10 NR
0.164 [kg]

8057711595709
Cardboard
500 NR
8.2 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.