



ECK81004

Residential > Utility series > Items for domestic use > Adaptors
> Socket outlet combination > Smart plug



Technical Symbols/Marks/Approvals

IP20	UL94 V0	GWT 750°	CE	RoHS II		MADE IN PRC
------	------------	-------------	----	---------	--	-------------------

Norms

CEI 23-50 CEI 23-151

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9003	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	White
Transparent	No	Impact strength	IK09	Working temperature	-15-35 °C
Compatible with Apple HomeKit	No	Compatible with Google Assistant	Yes	Compatible with Amazon Alexa	Yes
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	Yes	Rotated central insert	No	Nominal current	16 A
Number of socket outlets with protective contact CEE 7/3 (type F)	1	Number of socket outlets British Standard BS 1363	0	Number of socket outlets Italian standard type Bipasso	1
Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Type of mains connection	Italian type P17
NEMA designation	None	Housing shape	Square	Number of socket outlets CEE 7/1 (no protective contact)	0
Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	1	Number of cold device socket outlets	0
Number of socket outlets Danish standard (earthing pin, type K)	0	Number of socket outlets with protective contact CEE 7/5 (type E)	0	Number of NEMA-outlets	0
Residual current circuit breaker (RCCB)	No	Mains filter	No	Number of USB connections	0
Overcurrent protection	No	Max. connected load	3500 W	With cover	No
Type of plug	Straight	Directly pluggable (without power cord)	Yes		

Barcode



8056351665483

Unit

1 NR

0.06x0.053x0.09 [m]

0.1292 [kg]



8056351665490

Pack

12 NR

0.195x0.375x0.65 [m]

1.5504 [kg]



8056351665506

Cardboard

48 NR

0.2x0.395x0.28 [m]

6.2016 [kg]