

ECK81020

RESIDUAL CURRENT DEVICE 2P 30 MA 25A - 4,5 KA

Industrial > Distribution boards > Distribution boards > Mcb's - rcd's > Residual current circuit breaker (rccb)



Technical Symbols/Marks/Approvals



Norms

CEI EN 60898-1 CEI EN 61008-1 CEI EN 61009-1

Etim

GROUP EG000020 - Circuit breakers and fuses

CLASS EC000003 - Residual current circuit breaker (RCCB)

Number of poles	2	Rated voltage	230 V	Rated current	25 A
Rated fault current	0.03 A	Rated insulation voltage Ui	440 V	Rated impulse withstand voltage Uimp	4 kV
Power loss	5 W	Mounting method	DIN rail	Leakage current type	AC
Selective protection	No	Short-time delayed tripping	No	Surge current capacity	0.25 kA
Voltage type	AC	With interlocking device	No	Frequency	50/60 Hz
Additional equipment possible	Yes	Degree of protection (IP)	IP20	Width in number of modular spacings	2
Built-in depth	43.7 mm	Ambient temperature during operating	-25-40 °C	Pollution degree	2
Connectable conductor cross section multi-wired	25-25 mm ²	Connectable conductor cross section solid-core	35-35 mm ²	RAL-number (similar)	7035
Explosion-proof	No				

Barcode



8053676570300

Unit

1 NR

0.24 [kg]