elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECL4081

USB CHARGER - KEYSTONE DOCKING 2.1A

Residential > Wiring devices > Mylife > Mylife devices black > Usb power supply

Technical Symbols/Marks/Approvals

CE | IP20 | GWT 850°

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC002949 - USB power supply

Mounting method	Flush-mounted	**Anti-bacterial treatment**	No	**Colour**	Black
Model	Bus	**Suitable for degree of protection (IP)**	IP20	**Device width**	22
Device height	46.77	**Device depth**	44	**Min. depth of built-in installation box**	44
Number of ports USB-A	1	**Number of ports USB-C**	0	**Max. output current**	2100 mA

Documentation available for download



Instruction booklet

ECL4081AC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8053676574919
Unit
1 NR
0.0729 [kg]



8059606158600
Pack
6 NR
0.19x0.1x0.05 [m]
0.4374 [kg]



8032636768520
Cardboard
120 NR
0.215x0.4x0.31 [m]
8.748 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.