





MINITRUNKING HINGED LID AND SELF-ADHES. BOTTOM 12.5X12.5 BAGS OF 10 BARS









IK 04	IP 40	<u>UL94</u> V0	GWT 960 °	CE	RoHS II	MADE IN ITALY
--------------	--------------	--------------------------	---------------------	----	---------	---------------------

Norms

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. With adhesive strip for permanent attachment. Integrated lid with snap closure.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality Poly	rinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Transparent	No	Impact strength	IK04
Type of fastening	Self-adhesive	Width	12.5 mm	Height	12.5 mm
Length	2 m	Usable cross section	102 mm ²	RAL-number	9001
With protective foil	No	Working temperature	-5-60 °C	Cover model	With film hinge
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partition	s 0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				





Barcode



8056351667944

Pack

20 MT

1.4 [kg]



8056351668200

Cardboard

160 MT

11.2 [kg]