elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC20104

VARIABLE EXTERNAL ANGLE 70X20 SLATE RAL 7021

Trunkings > Wall and ceiling > Skirting and wall trunkings > Series 20 - trunking fittings > External bend for skirting trunkings

Technical Symbols/Marks/Approvals

IP40 | IK08 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-1

Description

External angle, quickly attached with screws, which allows for insulation and continuous separation of cables within their compartments. Rigid cover, adjustable from 60° to 120°, snaps on. Designed with rounded lines and no sharp edges to minimize accidental impacts and the possibility of detachment from the trunking.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000849 - Outer corner for skirting duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Colour**	Anthracite	**Impact strength**	IK08
Height	70 mm	**Depth**	20 mm	**Model**	Top cover
RAL-number	7021	**Sealing lip cover**	None	**Decoration**	None
With carpet border	No	**Angle**	60 ÷ 120 °		

Documentation available for download



Certification

Battiscopa Serie 20.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880880959

Pack

5 NR

0.1 [kg]



8054320280088

Cardboard

25 NR

0.165x0.175x0.105 [m]

0.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.