

ECRM50-48

FOR CONDUITS Ø 50 mm - MOUNTING HOLE Ø 47 mm - 5 PIECE BAG

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Plug conduit - box > Conduit-box joints

Technical Symbols/Marks/Approvals

IP44 | UL94 V0 | GWT 960° | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a junction box, made of soft PVC-based technopolymer. IP44 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Pipe diameter 50 mm - Box hole diameter 48 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	50 ÷ 50 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	Other
Number of conduit lead-ins	1				

Technical Characteristics

Box hole diameter	48 mm

Dimensions and technical drawings

ECRM50-48.2026.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054320286646
Pack
5 NR
0.232 [kg]

8057711597444
Cardboard
70 NR
0.39x0.295x0.21 [m]
3.248 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.