elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECSE8981

USB CHARGER - KEYSTONE DOCKING TYPE A

Residential > Wiring devices > Easy > Easy devices > Usb power supply

Technical Symbols/Marks/Approvals

CE | IP20 | GWT 850°

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC002949 - USB power supply

Mounting method	Flush-mounted	**Anti-bacterial treatment**	No	**Colour**	White
Model	Bus	**Suitable for degree of protection (IP)**	IP20	**Device width**	23 mm
Device height	47 mm	**Device depth**	46 mm	**Min. depth of built-in installation box**	46 mm
Number of ports USB-A	1	**Number of ports USB-C**	0	**Max. output current**	2100 mA

Documentation available for download




Instruction booklet

ECSE8981A-C.pdf

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050507870400
Unit
1 NR
0.0729 [kg]



8054382041771
Pack
6 NR
0.19x0.1x0.05 [m]
0.4374 [kg]



8056351668873
Cardboard
120 NR
0.215x0.4x0.31 [m]
8.748 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.