elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

# ECSH8060

## HALOGEN FREE SLOTTED TRUNKING WITH COVER 4/6/4 DIM. 80X60

Trunkings > Panelboards systems > Cable management > Slotted trunkings halogen free > Slotted cable trunking > Light grey - type s - narrow slots 4/6/4

### Technical Symbols/Marks/Approvals

HF | UL94 V2 | GWT 960° | -25° | +90° | CE | RoHS II | MADE IN ITALY

### Norms

EN 50267-2-1 EN 50267-2-2 IEC 60754-1 IEC 60754-2 EN 50085-1

EN 50085-2-3 UL 1565

## Description

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensional stability between -25°C and +90°C. Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

## Etim

### GROUP EG000007 - Slotted cable trunking system

### CLASS EC000012 - Slotted cable trunking system

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Other | **Halogen free** | Yes | **Colour** | Grey |
| **Type of fastening** | Bottom perforation | **Width** | 80 mm | **Height** | 60 mm |
| **Length** | 2000 mm | **Diameter** | 0 mm | **Distance of slots** | 6 mm |
| **Slit width** | 4 mm | **Type of side wall** | Hole-/slot punching | **Self-extinguishing** | Yes |
| **Flexible** | No | **Usable cross section** | 4202 mm² | **With cover/lid** | Yes |
| **RAL-number** | 7035 | | | | |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Documentation available for download



Certification

Canali tipo SH-AH - Analysis Test Report.pdf

## Barcode

8054320286158

**Cardboard**

28 MT

0.26x0.18x2.027 [m]

16.5004 [kg]

8055035960654

**Pallet**

504 MT

1.2x0.8x2.2 [m]

297.0072 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.