

ECTC1532TB

PLIABLE PVC CONDUIT 33212 Ø32 mm - 25 m WITH DRAW TAPE - WHITE



IMMAGINE
RAPPRESENTATIVA

EC

REPRESENTATIVE
IMAGE

Conduits and fittings > Conduits > Corrugated conduits >
Series tc15 - pvc - class 33212 - 750 n > plastic conduits >
White - cable puller

Technical Symbols/Marks/Approvals

UL94 V0	GWT 960°	CE	RoHS II	MADE IN ITALY
------------	-------------	----	---------	---------------------

Norms

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	White	RAL-number	9002	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	23.5 mm
Outer diameter	32 mm	High conducting inner coating	No	With metre indication	No

Barcode




8054320285434

Cardboard

25 MT

0.5x0.5x0.15 [m]

3.235 [kg]



8057711598182

Pallet

1600 MT

0.8x1.2x2.5 [m]

207.04 [kg]