

# ECTC182010

## PLIABLE PVC CONDUIT 33412 Ø20 mm - 10 m

Conduits and fittings > Conduits > Corrugated conduits > Series tc18 - pvc -25°c - class 33412 - 750 n > plastic conduits > Grey - 10 meters-roll

### Technical Symbols/Marks/Approvals

UL94 V0 | GWT 960° | ÖVE | CE | -25° | MADE IN ITALY

### Norms

EN 61386-1 EN 61386-22

## Description

Flexible corrugated protective conduit made of impact-resistant PVC-based technopolymer. Flame propagation resistance: self-extinguishing in less than 30". Resistance to abnormal heat: up to 960°C (GWT IEC 60695-2-11 standard). Minimum operating temperature -25°C. Compression resistance 750 N. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: medium -33412 according to EN 61386-1, EN 61386-22 standards. Not micro-hole free. Not suitable for liquid concrete.
Nominal outside diameter 20 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC001174 - Plastic installation tube

| | | | | | |
|---|---|---|---|---|---|
| **Flush-mounted installation** | Yes | **Material** | Polyvinyl chloride (PVC) | **Halogen free** | No |
| **Colour** | Grey | **RAL-number** | 7031 | **UV resistant** | No |
| **Suitable for underground installation** | No | **Operating temperature** | -25 ÷ 60 °C | **Bending strength** | Pliable |
| **Compressive strength class according to EN 61386-1** | Medium (class 3 / 2 Joule) | **Impact strength class according to EN 61386-1** | Medium (class 3 / 2 Joule) | **With sleeve** | No |
| **Fire retardant version** | Yes | **Surface mounting** | No | **Suitable for installation on wood** | No |
| **Suitable for hollow wall installation** | No | **Suitable for concrete installation** | Yes | **Machine and systems installation** | No |
| **Suitable for underfloor installation (screed)** | No | **Suitable for outdoor installation** | No | **Inner diameter** | 13.4 mm |
| **Outer diameter** | 20 mm | **High conducting inner coating** | No | **With metre indication** | No |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Documentation available for download



**Certification**

OVE_50017-002-10.pdf

## Barcode

barcode

8032793879466

**Unit**

1 NR

0.6994 [kg]

8033576778952

**Pallet**

216 NR

151.0704 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.