elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECTFLEX25

CAP FOR PLIABLE CONDUIT Ø25 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Sealing plug

Technical Symbols/Marks/Approvals

HF | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21 EN 61386-22

Description

Polyethylene sealing plug
For double insulation of wall-mounted boxes sizes C9-C10 and vertical interlocked socket-outlets

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001491 - Closure plug for installation tube

Material	Plastic	**Material quality**	Polyethylene (PE)	**Colour**	Other
For nominal tube diameter	25 ÷ 25 mm	**Suitable for rigid tubes**	No	**Suitable for flexible tubes**	Yes
Suitable for pliable tubes	Yes	**Airtight**	Yes	**Pushthrough membrane**	No

Barcode

8054320285168
Pack
100 NR
0.13 [kg]

barcode

8057711598458
Cardboard
1500 NR
1.95 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.