
elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECTG1250

RIGID CONDUIT 22211 Ø50 mm - 3 m - BUNDLE 15

Conduits and fittings > Conduits > Rigid conduits > Series tg12 - pvc - class 22211 - 320 n > plastic conduits > 3 meters - lenght

Technical Symbols/Marks/Approvals

UL94 V0 | UV | GWT 960° | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Rigid protective conduit made of impact-resistant PVC-based technopolymer. Flame propagation resistance: self-extinguishing in less than 30". Resistance to abnormal heat: up to 960°C (GWT IEC 60695-2-11 standard). UV resistant. Compression resistance 320 N. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: light -22212 according to EN 61386-1, EN 61386-21 standards.
Nominal outside diameter 50 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	**Material**	Polyvinyl chloride (PVC)	**Halogen free**	No
Colour	Grey	**RAL-number**	7035	**UV resistant**	Yes
Suitable for underground installation	No	**Operating temperature**	-5 ÷ 60 °C	**Bending strength**	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	**Impact strength class according to EN 61386-1**	Light (class 2 / 1 Joule)	**With sleeve**	No
Fire retardant version	Yes	**Surface mounting**	Yes	**Suitable for installation on wood**	Yes
Suitable for hollow wall installation	Yes	**Suitable for concrete installation**	No	**Machine and systems installation**	No
Suitable for underfloor installation (screed)	No	**Suitable for outdoor installation**	No	**Inner diameter**	46.4 mm
Outer diameter	50 mm	**High conducting inner coating**	No	**With metre indication**	No

Technical Characteristics


Lunghezza Barra	3 m

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054320284925
Cardboard
15 MT
5.6205 [kg]



8057711598694
Pallet
360 MT
134.892 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.