

ECTG2025B

HF RIGID CONDUIT 22431 Ø25 mm - 3 m - BELL END



Conduits and fittings > Conduits > Rigid conduits > Series tg20
- pp - class 22431 - 320 n > Plastic installation tube > 3mt-
length - bell end



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

HF

+90°



RoHS II

MADE
IN
ITALY

Norms

EN 61386-1 EN 61386-21 IEC 60754-1 IEC 60754-2 EN 61034-2

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-105 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	Yes
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	21.7 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Barcode




8054320284611

Cardboard

60 MT

7.224 [kg]



8057711598991

Pallet

1440 MT

3x0.61x0.62 [m]

173.376 [kg]