



EC20311

8-MODULE TOWER ADAPTOR BOX 108 mm HOLE C.E DISTANCE-SLATE RAL 7021



Trunkings > Wall and ceiling > Skirting and wall trunkings > Serie 20 - trunking fittings > Modular boxes for wiring devices

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

The 4+4 module 108.5 mm center-to-center appliance box can be used to install up to 8 Italian standard appliances or 4 multi-standard sockets. A row, with the supplied accessories, can be reduced to 3 modules. The large internal volume allows for the installation of any appliance. The box is composed of three assembled parts: the lower part, which snaps onto the trunking and the wall with 4 screws, and serves as an insulating base and a grid separating the various circuits. The upper part is appropriately shaped to accommodate the appliance fixing frames. The trunking cover, in addition to its protective function, gives the whole a harmonious and elegant shape.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling


CLASS EC000079 - Appliance box for skirting duct

Degree of protection (IP)	IP40	Mounting direction	Horizontal	Material	Plastic
Halogen free	Yes	Anti-bacterial treatment	No	Colour	Anthracite
Impact strength	IK08	RAL-number	7021	Working temperature	-5-60 °C
Decoration	None	Mounting method installation unit	Standard	Height baseboard duct	130 mm
Depth plinth skirting duct	28 mm	Number of device units	8	Equipped with	None

Technical Characteristics

dimensions 170 x 340 x 50 mm

Documentation available for download



Barcode



8032793876823

Unit

1 NR

0.505 [kg]



8059307212830

Cardboard

4 NR

0.39x0.295x0.21 [m]

2.02 [kg]