

EC22016555-3



TRUNKING WITH COVER DIM. 165X55 - 3 COVERS - WHITE

Trunkings > Wall and ceiling > Wiring device trunkings > Series kuadra - for 45x45 devices > Device installation trunkings



Technical Symbols/Marks/Approvals

IK08	IP40	UL94 V0	GWT 960°	CE	RoHS II	NF	MADE IN ITALY
------	------	------------	-------------	----	---------	----	---------------------

Norms

EN 50085-1 EN 50085-2-1

Description

Cable and device trunking made of self-extinguishing rigid PVC technopolymer. For standard 45x45 mm devices with direct mounting to the trunking. Bottom pre-drilled for fixing with screws and anchors. Front-mounted cover included. The trunking and cover are covered with a transparent protective film.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK08	Width	165 mm
Depth	55 mm	Length	2 m	Usable cross section	7544 mm²
RAL-number	9001	Mounting method cover	Inner lying	With protective foil	Yes
Working temperature	-5-60 °C	Number of plug-in partitions	6	With cable fixing clip	No
With duct connector	No	Bottom perforation	No	Number of covers	3
Cover width 1	45 mm	Cover width 2	45 mm	Cover width 3	45 mm
Symmetric	Yes	Covers included	Yes	Construction type rectangular	Yes
Construction rear wall (inner side)	Perforated				

Documentation available for download



Barcode



8050880881130

Cardboard

16 MT

0.26x0.18x2.027 [m]

31 [kg]