elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC2209055

TRUNKING WITH COVER DIM. 90X55 - 1 COVER - WHITE

Trunkings > Wiring device trunkings > Series kuadra - for 45x45 devices > Series kuadra - for 45x45 devices > Device installation trunkings

Technical Symbols/Marks/Approvals

IP40 | IK08 | UL94 V0 | GWT 960° | CE | RoHS II | NF | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-1

Description

Cable and device trunking made of self-extinguishing rigid PVC technopolymer. For standard 45x45 mm devices with direct mounting to the trunking. Bottom pre-drilled for fixing with screws and anchors. Front-mounted cover included. The trunking and cover are covered with a transparent protective film.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Polyvinyl chloride (PVC)
Halogen free	No	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK08	**Width**	90 mm
Depth	55 mm	**Length**	2000 mm	**Usable cross section**	4003 mm²
RAL-number	9001	**Mounting method cover**	Inner lying	**With protective foil**	Yes
Working temperature	-5 ÷ 60 °C	**Number of plug-in partitions**	2	**With cable fixing clip**	No
With duct connector	No	**Bottom perforation**	No	**Number of covers**	1
Cover width 1	45 mm	**Cover width 2**	0 mm	**Cover width 3**	0 mm
Symmetric	Yes	**Covers included**	Yes	**Construction type rectangular**	Yes
Construction rear wall (inner side)	Perforated				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

LICENCE 669929 KUADRA.pdf

Barcode

8050880881147

Cardboard

24 MT

0.26x0.26x2.03 [m]

22.9992 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.