



EC220AI16555

VARIABLE INTERNAL ANGLE DIM. 165X55 mm

Trunkings > Wall and ceiling > Wiring device trunkings > Series kuadra - for 45x45 devices > Inner bend for device installation trunkings



Technical Symbols/Marks/Approvals

IK08	IP40	GW 650°	CE	RoHS II	NF	MADE IN ITALY
------	------	------------	----	---------	----	---------------------

Norms

EN 50085-1 EN 50085-2-1

Description

Variable internal angle for direction changes from 60° to 120°. Snaps onto the channel. Consists of two pieces.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000867 - Inner corner for wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK08	Width	165 mm
Depth	55 mm	Model	Moulded hood	RAL-number	9001
Mounting method cover	Spanned	With protective foil	No	Working temperature	-5-60 °C
With cable fixing clip	No	With duct connector	Yes	Shape	Symmetric
Bottom perforation	No	Angle	60-120 °	Number of covers	1
Cover width 1	165 mm				

Documentation available for download



Barcode



8033576778990

Unit

1 NR

0.23 [kg]



8059307212915

Cardboard

10 NR

0.39x0.295x0.3 [m]

2.3 [kg]