



## EC23404

### FLEXIBLE SLOTTED TRUNKING SCREW FIXING 25X25X500

Trunkings > Panelboards systems > Cable management > Flexible slotted trunkings > Flexible slotted cable trunkings > Punched fixing holes

#### Technical Symbols/Marks/Approvals



#### Norms

EN 50085-1 EN 50085-2-3 UL 1565

## Description

Flexible wiring duct made of self-extinguishing UL94-V2 polypropylene technopolymer. Pre-drilled bottom for installation with fixing screws.

## Etim

**GROUP EG000007 - Slotted cable trunking system**

**CLASS EC000012 - Slotted cable trunking system**

|                             |                     |                           |           |                   |        |
|-----------------------------|---------------------|---------------------------|-----------|-------------------|--------|
| <b>Material</b>             | Polypropylene (PP)  | <b>Halogen free</b>       | <b>No</b> | <b>Colour</b>     | Grey   |
| <b>Type of fastening</b>    | Bottom perforation  | <b>Width</b>              | 25 mm     | <b>Height</b>     | 25 mm  |
| <b>Length</b>               | 500 mm              | <b>Distance of slots</b>  | 7.5 mm    | <b>Slit width</b> | 7.5 mm |
| <b>Type of side wall</b>    | Slotted             | <b>Self-extinguishing</b> | Yes       | <b>Flexible</b>   | Yes    |
| <b>Usable cross section</b> | 552 mm <sup>2</sup> | <b>With cover</b>         | Yes       | <b>RAL-number</b> | 7030   |

## Barcode



8050880881284

**Cardboard**

70 NR

2.597 [kg]