

## EC350C5P

### FLUSH MOUNTING JUNCTION BOX WITH COVER AND PROTECTION LID DIM. 160X130X70



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Enclosures > Recessed > Recessed junction boxes > Series 350 - masonry > Flush mount junction boxes > Orange boxes - mortar guard

#### Technical Symbols/Marks/Approvals

|      |    |             |    |         |  |                     |
|------|----|-------------|----|---------|--|---------------------|
| IP40 | HF | GWT<br>650° | CE | RoHS II |  | MADE<br>IN<br>ITALY |
|------|----|-------------|----|---------|--|---------------------|

#### Norms

EN 60670-1 EN 60670-22

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

|                                           |             |                                       |                    |                                |             |
|-------------------------------------------|-------------|---------------------------------------|--------------------|--------------------------------|-------------|
| Max. conductor cross section              | 0           | Mounting method                       | Flush-mounted      | Degree of protection (IP)      | IP40        |
| Material                                  | Plastic     | Halogen free                          | Yes                | Surface protection             | Untreated   |
| Colour                                    | Orange      | Width                                 | 161 mm             | Model                          | Other       |
| Length                                    | 130 mm      | Diameter                              | 0 mm               | Cover model                    | Blind cover |
| Inner depth                               | 69 mm       | Circuit integrity                     | None               | Equipped with                  | None        |
| Shape                                     | Rectangular | Number of inlets                      | 15                 | Inlet from the rear            | Yes         |
| Compliant with BS 4662                    | No          | Couplable                             | No                 | Transparent cover              | No          |
| Pipe locking                              | No          | Construction type                     | Cable junction box | Airtight                       | No          |
| For tube diameter                         | Other       | Cover attachment                      | Screwed            | Sealable                       | No          |
| With screening                            | No          | Provided with revolving ring          | No                 | Depth                          | 0-69 mm     |
| For number of device inserts              | 0           | Mounting switching equipment          | Screwing           | With screws                    | Yes         |
| Housing feed-through by break-out opening | Yes         | Housing feed-through by seal membrane | No                 | Housing feed-through by nozzle | No          |
| Housing feed-through by step membrane     | No          | Pipe locking optional                 | No                 | Number of included spouts      | 0           |
| Number of poles of the clamp              | 0           | Clamp position fixed                  | No                 | Luminaire hook mounting        | No          |
| Nozzle                                    | None        | Special application                   | None               | With partition panel           | No          |

## Technical Characteristics

Preparation for  
compartments/DIN rails

3

## Documentation available for download



## Barcode



8032793872863

**Unit**

1 NR

0.1863 [kg]



8059307213288

**Cardboard**

60 NR

0.605x0.405x0.55 [m]

11.178 [kg]