

# EC350C7BL

## FLUSH MOUNTING JUNCTION BOX WITH LID DIM. 294X152X70 BLUE

Enclosures > Recessed > Recessed junction boxes > Series 350 - masonry > Flush mount junction boxes > Blue boxes

### Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY

### Norms

EN 60670-1 EN 60670-22

## Description

Recessed junction box for masonry walls. Made of impact-resistant, halogen-free technopolymer. Complete with lid and fixing screws. Paintable embossed lid. Resistance to abnormal heat up to 650°C (GWT). Manufactured in accordance with EN 60670-1:2005, EN 60670-22:2006. Installation temperatures: minimum -15°C, maximum +60°C. IP40 protection rating.
Dimensions: 294x152x70 mm
Designed for 3 compartments



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

| | | | | | |
|---|---|---|---|---|---|
| **Max. conductor cross section** | 0 | **Mounting method** | Flush-mounted | **Degree of protection (IP)** | IP40 |
| **Material** | Plastic | **Halogen free** | Yes | **Surface protection** | Untreated |
| **Colour** | Blue | **Width** | 295 mm | **Model** | Other |
| **Length** | 152 mm | **Diameter** | 0 mm | **Cover model** | Blind cover |
| **Inner depth** | 69 mm | **Circuit integrity** | None | **Equipped with** | None |
| **Shape** | Rectangular | **Number of inlets** | 26 | **Inlet from the rear** | Yes |
| **Compliant with BS 4662** | No | **Couplable** | No | **Transparent cover** | No |
| **Pipe locking** | No | **Construction type** | Cable junction box | **Airtight** | No |
| **For tube diameter** | Other | **Cover attachment** | Screwed | **Sealable** | No |
| **With screening** | No | **Provided with revolving ring** | No | **Depth** | 0 ÷ 69 mm |
| **For number of device inserts** | 0 | **Mounting switching equipment** | Screwing | **With screws** | Yes |
| **Housing feed-through by break-out opening** | Yes | **Housing feed-through by seal membrane** | No | **Housing feed-through by nozzle** | No |
| **Housing feed-through by step membrane** | No | **Pipe locking optional** | No | **Number of included spouts** | 0 |
| **Number of poles of the clamp** | 0 | **Clamp position fixed** | No | **Luminaire hook mounting** | No |
| **Nozzle** | None | **Special application** | None | **With partition panel** | No |

## Technical Characteristics

| | |
|---|---|
| **Preparation for compartments/DIN rails** | 3/- |

## Documentation available for download



Certification

Serie 350
IMQ_CA02.01670_
2018.pdf

## Dimensions and technical drawings

EC350C7_2026.pdf



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8056351660952
**Unit**
1 NR
0.3714 [kg]

8056351661065
**Cardboard**
28 NR
0.605x0.405x0.55 [m]
10.3992 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.