elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

EC351C1

SPARE LID FOR FLUSH MOUNTING DIM. 92X92



Enclosures > Recessed > Recessed junction boxes > Series 351 - spare cover lids > Cover lids

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-22

Description

Replacement cover for flush-mounted junction boxes. Made of impact-resistant, halogen-free technopolymer. Complete with fixing screws. Embossed, paintable cover. Resistance to abnormal heat up to 650°C (GWT). Manufactured in compliance with EN 60670-1:2005, EN 60670-22:2006. Installation temperatures: minimum -15°C, maximum +60°C. IP40 protection rating.
Dimensions: 115x115 mm
For C1 boxes

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002656 - Cover for box/housing for built-in mounting in the wall/ceiling

RAL-number (similar)	9001	**Material**	Plastic	**Halogen free**	Yes
Colour	White	**Type of fastening**	Cover for mounting with screws	**Width**	115 mm
Depth	3.2 mm	**Model**	Blind cover	**Length**	115 mm
Diameter	0 mm	**Shape**	Square	**Sealable**	No
With screws	Yes	**For box-/housing diameter**	0 ÷ 0 mm	**For box-/housing length**	91 mm
For box-/housing width	91 mm	**With cable outlet**	No		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032636760692

Unit

1 NR

0.03 [kg]



8059307213332

Cardboard

200 NR

0.39x0.295x0.21 [m]

6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.