

EC37111

PLASTIC SPACER FOR RECTANGULAR BOX 37100 DIM. 40 mm

Enclosures > Recessed > Boxes for wiring devices > Series 37 - masonry recessed boxes > Accessories for junction boxes

Technical Symbols/Marks/Approvals

HF | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 60670-1 CEI 23-74

Description

Spacer for joining flush-mounting boxes for masonry walls, series 37100-37104-37106. For the perfect installation of horizontal or vertical box banks. Made of shock-resistant, halogen-free technopolymer in yellow. Resistance to abnormal heat: 650°C (Glow Wire Test - GWT). Installation temperatures: minimum –15°C, maximum +60°C.
Dimensions: 40 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall

Type of accessory/spare part	Other	**Accessory**	Yes	**Spare part**	No
Suitable for built-in installation box	Yes	**Suitable for central conduit box**	No		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880881406
Pack
20 NR
0.08 [kg]

8057711590070
Cardboard
200 NR
0.39x0.295x0.21 [m]
0.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.