

EC400C9A

SELF-EXTINGUISHING JUNCTION BOX IP55 WITH STEPPED GLANDS DIM. 380X300X120



Enclosures > Wall-mount > Wall-mount junction boxes > Series 400 - nipple version > Wall mount junction boxes > Ip55 - self-extinguishing v0

Technical Symbols/Marks/Approvals

IP55	UL94 V0	GWT 960°	IK08	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------------

Norms

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP55
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	380 mm	Depth	120 mm
Model	Junction box	Length	300 mm	Diameter	0 mm
Working temperature	-25-70 °	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	12
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	40 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Trimable step membrane	Cover attachment	Screwed	Castable	No
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Yes				

Documentation available for download



Barcode



8032636761170

Unit

1 NR

2 [kg]



8059307213509

Cardboard

4 NR

0.605x0.4x0.36 [m]

8 [kg]