elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET




IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

ECS10080B

SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 100X80 WHITE

Trunkings > Panelboards systems > Cable management > Slotted trunkings > Slotted cable trunking > White - type s - narrow slots 4/6/4

Technical Symbols/Marks/Approvals

UL94 V0 | GWT 960° | CE | RoHS II | | | RINA | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	**Halogen free**	No	**Colour**	White
Type of fastening	Bottom perforation	**Width**	100 mm	**Height**	80 mm
Length	2000 mm	**Diameter**	0 mm	**Distance of slots**	6 mm
Slit width	4 mm	**Type of side wall**	Hole-/slot punching	**Self-extinguishing**	Yes
Flexible	No	**Usable cross section**	7156 mm²	**With cover/lid**	Yes
RAL-number	9001				

Technical Characteristics

Separator predisposition	SI (2)

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Certificato UL A-S ATL AMF E331386.pdf



Certification

RINA DCMTVL_1005538_380865962_2025.PDF



Certification

Canali asolati tipo S IMQ_EI617_2020.pdf

Barcode

8059307211635

Cardboard

24 MT

0.26x0.26x2.03 [m]

24 [kg]

8055035960173

Pallet

288 MT

1.2x0.8x2.2 [m]

288 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.