

EC492C8A



SELF-EXTINGUISHING SMOOTH SIDED BOX IP67 DIM. 310x250x125 - 1/4 TURN

Enclosures > Wall-mounted > Junction boxes > 49 - 1/4 turn plastic screw > Protected and watertight wall/series junction boxes > Smooth walls - ip67 - self-extinguishing v0



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

IP67

IK08

V0

GWT
950°

Norms

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Model	Junction box	Material	Plastic	Surface protection	Untreated
Length	230 mm	Colour	Grey	Width	310 mm
Depth	125 mm	Halogen free	No	Degree of protection (IP)	IP67
Equipped with	None	Shape	Rectangular	Diameter	0 mm
Mounting method	Wall-/ceiling mounting	For tube diameter	Other	Inlet from the rear	No
Number of inlets	0	Cover model	Blind cover	Transparent cover	No
Cover attachment	Other	Sealable	Yes	Circuit integrity	None
With screening	No	Mounting in the soil	No	Mounting under water	No
Connectable	No	Type of housing feed-through	None	Castable	Yes
Casting compound included	No	Rated insulation voltage Ui	1000 V	Weatherproof	Yes
Explosion-tested version	No	For Ex-zone gas	None	For Ex-zone dust	None
Operating temperature	-25-70 °C				

Documentation available for download



Brochure

DEF Brochure
cassette IT MR
doppie (2).pdf

CASSETTE DI DERIVAZIONE
IP67 CON VITI 1/4 DI GIRO
PROTEZIONE E PRATICA

elettrocanali

0000

Barcode



8050507876167

6 NR

6.123 [kg]



8050507875863

1 NR

1.0205 [kg]