elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC52009

PG THREAD LOCK NUT PG 9

Enclosures > Accessories > Accessories > Cable glands > Locknut for cable gland > Pg pitch

Technical Symbols/Marks/Approvals

GWT 650° | HF | CE | RoHS II | MADE IN ITALY

Description

PG9 threaded locknut. Made of polyamide PA6.6. Glow Wire Test (GWT) resistance up to 650°C.

Etim

GROUP EG000009 - Cable and wire entry systems

CLASS EC000940 - Locknut for cable screw gland

Material	Plastic	**Material quality**	Polyamide (PA)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Height**	5 mm
Thread type	PG	**Nominal thread size metric/PG**	9	**Pitch thread**	1.41 mm
Glass-fibre reinforced	No	**Shock resistant**	No	**Shape**	Hexagonal
With earthing connection	No				

Technical Characteristics

Mounting hole diameter	15.5 mm	**diametro_di_serraggio**	4 - 8 mm

Barcode

8050880882052
Pack
50 NR
0.105 [kg]

8057711590506
Cardboard
1000 NR
0.39x0.295x0.21 [m]
2.1 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.