elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC52216

PG THREAD CAP PG16

Enclosures > Accessories > Accessories > Modular enclosure accessories > Sealing cap > Pg pitch

Technical Symbols/Marks/Approvals

GWT 650° | HF | CE | RoHS II | MADE IN ITALY

Description

PG16 threaded plug with screwdriver slot. Made of polyamide PA6.6. Resistance to abnormal heat up to 650°C (GWT).
Diameter 27.0 mm
Height 10.3 mm
Thread length 6.0 mm

Etim

GROUP EG000009 - Cable and wire entry systems

CLASS EC000032 - Plug for cable screw gland

Material	Plastic	**Material quality**	Polyamide (PA)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**RAL-number**	7035
Working temperature	-25 ÷ 70 °C	**Thread type**	PG	**Nominal thread size metric/PG**	16
Pitch thread	1.41 mm	**Glass-fibre reinforced**	No	**Shock resistant**	No
Explosion-tested version	No	**For Ex-zone gas**	None	**For Ex-zone dust**	None
Pressure-compensating	No				

Technical Characteristics

height	10.3 mm	**cap diameter**	27.0 mm	**thread length**	6.0 mm

Barcode

8050880882274
Pack
100 NR
0.4 [kg]

8057711590728
Cardboard
1000 NR
4 [kg]

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.