

EC60024B

WALL-MOUNT MODULAR ENCLOSURE IP40 DIM.280X350X100 24 MOD. WHITE TRAN.DOOR

Enclosures > Wall-mount > Wall modular enclosures > Series 600 - ip40 modular enclosures > Small distribution board > White

Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Wall-mounted consumer unit. Made of shockproof UV-resistant and halogen-free ABS-based technopolymer. Impact resistance rating IK08. Resistance to abnormal heat up to 650°C (GWT). Base and cover in halogen-free ABS-based technopolymer. Reversible cover. Smoked polycarbonate door. Self-adhesive circuit identification label included. Blanking plates for unused modules included. Fixing screw caps provided to maintain IP protection rating and double insulation. Mounted galvanized steel DIN rail. Manufactured in compliance with EN 60670-1:2005 and EN 60670-22:2013 standards. Installation temperatures: minimum –5°C, maximum +60°C. Operating temperatures: minimum -25°C, maximum +70°C. IP40 protection rating.
External dimensions 280x350x100 mm
24 DIN modules (2x12)
Power dissipation 30 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	24
Colour	White	**Width**	280 mm	**Height**	350 mm
Depth	100 mm	**RAL-number**	9001	**UV resistant**	Yes
Type of covering	Door	**Cover model**	With notch	**Type of door**	Single
Transparent cover/door	Yes	**With lock**	No	**Inner depth**	100 mm
Number of rows	2	**Extension possible**	No	**Housing material**	Plastic
With mounting plate	No	**Signal passing door**	No	**Type of closure**	Other
Earthing terminal block	No	**Neutral terminal block**	No	**DIN-rail**	Yes
EMC-version	No				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Technical Characteristics

dimensions	280x350x100 mm	**Power dissipation**	30 W

Documentation available for download



Instruction booklet

Istruzioni 600-610_0423.pdf



Certification

Serie 600-610 IMQ_CA02.00428_2026.pdf

Dimensions and technical drawings

EC60024_2025.pdf

Barcode

8032636762740

Unit

1 NR

0.33x0.41x0.16 [m]

1.797 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.