elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**




# ECGFLEX16W05

## COUPLING FOR PLIABLE CONDUIT IP40 16 mm - TRANSLUCENT bag 5 pcs

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugeted conduits > Joints for corrugated conduits

### Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | NF | MADE IN ITALY

## Description

Joint for Halogen-Free polyethylene corrugated pipe. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C.
Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C.
Regulatory references: EN 61386-1, EN 61386-22.
Nominal internal diameter 16 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC001492 - Coupler for cable protection tube for underground application

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyethylene (PE) | **Halogen free** | Yes |
| **Surface protection** | Untreated | **Colour** | Colourless | **UV resistant** | No |
| **Surface polished** | No | **Separable** | No | **Inner diameter** | 15.9 mm |
| **Outer diameter** | 19.3 mm | **Nominal diameter, connection 1** | 16 mm | **Nominal diameter, connection 2** | 16 mm |
| **Reducing** | No | **With rubber seal** | No | | |

## Technical Characteristics

| | | | |
|---|---|---|---|
| **length** | 50 mm | **Tipologia** | sacchetto da 5 pezzi |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8032793878131

**Unit**

1 NR

0.0258 [kg]



8059307210874

**Cardboard**

400 NR

0.605x0.4x0.35 [m]

10.32 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.