

ECGS25W02

IP65 RIGID-FLEXIBLE SPIRAL CONDUIT JOINT Ø25/20 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit - spiral conduit > Conduit joints (spiral-rigid) - different diameters

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Description

Connector for the connection between a pipe and a spiral conduit of different diameters, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Pipe diameter 25 mm - Conduit diameter 20 mm

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001172 - Coupler for corrugated plastic hoses

Degree of protection (IP)	IP65	**Material**	Plastic	**Material quality**	Other
Colour	Grey	**Model**	Straight	**Working temperature**	-5 ÷ 60 °C
Nominal size	20 ÷ 25 mm				

Technical Characteristics

Tipologia	sacchetto da 2 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033954878687

Unit

1 NR

0.048 [kg]



8059307210935

Cardboard

100 NR

0.39x0.295x0.21 [m]

4.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.