elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCS25W02

IP65 90° BEND DIAM.20 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > 90° bend

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Description

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 25 mm - bending radius 85 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	25 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	25 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	85 mm	**Bend angle**	90 °		

Technical Characteristics

Tipologia	sacchetto da 2 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8033954878526

Unit

1 NR

0.09 [kg]

8059307210652

Cardboard

50 NR

0.39x0.295x0.3 [m]

4.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.