



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

ECCXS25W01

IP65 CONDUIT-BOX FLEXIBLE BEND DIAM.25 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > Ip65 flexible bend (conduits-box)



Technical Symbols/Marks/Approvals

IP65	UL94 V0	GWT 960°	IK07	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------------

Description

Flexible bend for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 25 mm - length 230 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	Material quality	Polyvinyl chloride (PVC)	Halogen free	No
Surface protection	Untreated	Colour	Grey	Model	Plug-in
Diameter	25 mm	Flexible	Yes	UV resistant	Yes
Quality of surface coating	Uncoated	Surface polished	No	Surface brushed	No
Compressive strength class according to EN 61386-1	None	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	For nominal tube diameter	25 mm
With sleeve	Yes	Two-part	No	With inspection opening and cover	No
Radius	250 mm	Bend angle	90 °		

Technical Characteristics

length	230 mm	Tipologia	sacchetto da 1 pezzo
---------------	--------	------------------	----------------------

Barcode



8033954878649

Unit

1 NR

0.0714 [kg]



8059307210737

Cardboard

140 NR

0.605x0.4x0.35 [m]

9.996 [kg]