



# ECCXT16W01

## IP65 CONDUIT-CONDUIT FLEXIBLE BEND DIAM.16 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > Flexible bend (conduits-conduits)

### Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

## Description

Flexible bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 16 mm - length 220 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC000936 - Bend for installation tubes

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyvinyl chloride (PVC) | **Halogen free** | No |
| **Surface protection** | Untreated | **Colour** | Grey | **Model** | Plug-in |
| **Diameter** | 16 mm | **Flexible** | Yes | **UV resistant** | Yes |
| **Quality of surface coating** | Uncoated | **Surface polished** | No | **Surface brushed** | No |
| **Compressive strength class according to EN 61386-1** | None | **Impact strength class according to EN 61386-1** | Medium (class 3 / 2 Joule) | **Suitable for nominal tube diameter** | 16 mm |
| **With sleeve** | Yes | **Two-part** | No | **With inspection opening and cover** | No |
| **Radius** | 160 mm | **Bend angle** | 90 ° | | |

## Technical Characteristics

| | | | |
|---|---|---|---|
| **length** | 220 mm | **Tipologia** | sacchetto da 1 pezzo |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8033954878540

**Unit**

1 NR

0.04 [kg]



8059307210751

**Cardboard**

200 NR

0.605x0.4x0.26 [m]

8 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.