

ECGX25W02

IP65 SPIRAL CONDUIT 25-BOX JOINT-GAS THREAD -1" - GREY -2 PZ

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Gas pitch - grey - bag of 2 pieces

Technical Symbols/Marks/Approvals

IP65 | UL94 V2 | GWT 750° | CE | RoHS II | | | MADE IN ITALY

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut.
Conduit 25 mm - 1" Thread

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	**Colour**	Grey	**Model**	Straight
Working temperature	-25 ÷ 65 °C	**Nominal diameter**	25 mm	**Material sealing**	No sealing
Nominal size in inch	1 inch	**Revolving thread**	Yes	**Construction type**	Internal thread
Type of connection	Thread	**One-piece**	Yes	**Material screw gland**	Polypropylene (PP)
Min. inner diameter hose	25 mm	**Approved in combination with protective conduit according to EN 61386-23**	Yes	**Approved in combination with protective conduit UR**	Yes

Technical Characteristics

Tipologia	sacchetto da 2 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8033954878717

Unit

1 NR

0.056 [kg]



8059307211017

Cardboard

75 NR

0.39x0.295x0.21 [m]

4.2 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.